

FEATURES

- Vented cast aluminum chassis for optimum strength and low compression
- Geometrically reinforced aluminum cone for optimum piston operation and reduced break-up.
- Soft low damping rubber surround for improved transient response
- Non-conducting fibre glass voice coil former for minimum damping
- Extended copper sleeve on pole piece for low inductance and low distortion
- CCAW voice coil for reduced moving mass
- Long life silver lead wires
- Vented pole piece for reduced compression

Specs :


Nominal Impedance	4 Ω	Free air resonance, F_s	30 Hz
DC resistance, R_e	3.1 Ω	Sensitivity (2.83 V / 1 m)	90 dB
Voice coil inductance, L_e	0.13 mH	Mechanical Q-factor, Q_{ms}	4.3
Effective piston area, S_d	118 cm ²	Electrical Q-factor, Q_{es}	0.31
Voice coil diameter	35.5 mm	Total Q-factor, Q_{ts}	0.29
Voice coil height	16 mm	Moving mass incl.air, M_{ms}	12.4 g
Air gap height	5 mm	Force factor, Bl	4.9 Tm
Linear coil travel (p-p)	11 mm	Equivalent volume, V_{as}	42.6 liters
Magnetic flux density	1.0 T	Compliance, C_{ms}	2.16 mm/N
Magnet weight	0.54 kg	Mechanical loss, R_{ms}	0.6 kg/s
Net weight	1.56 kg	Rated power handling*	60 W

* IEC 268-5, T/S parameters measured on drive units that are broken in.

Box recommendations :

Sealed box : -
Vented box : -

Conditions:



Response Curve :

— (Blue) : on axis — (Green) : 30° off-axis — (Red) : 60° off-axis

REV.4 (16.02.2016)